

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Hostalen CRP 100 RESIST CR W BLUE
CAS Number: 25087-34-7
Chemical characterization : Polyethylene copolymer
Chemical Name : 1-Butene, polymer with ethene
Synonyms : Ethylene, polymer with 1-butene, Ethene-Butene copolymer

Identified uses : Manufacture of plastic articles by injection molding, extrusion or other conversion process.

Prohibited uses : FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications

Company : Equistar Chemicals, LP
LyondellBasell Tower, Suite 300
1221 McKinney St.
P.O. Box 2583
Houston Texas 77252-2583

Telephone : Customer Service 888 777-0232
Product Safety 800 700-0946

Emergency telephone : CHEMTREC USA 800-424-9300
EQUISTAR 800-245-4532

E-mail address : product.safety@lyb.com

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

OSHA Hazard Category: Combustible Dust

Label elements**Signal Word** : Warning**Hazard Statements** : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.**Other hazards**

No additional information available.

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

3. Composition/information on ingredients**Mixtures****Ingredients**

Chemical Name	CAS-No.	Weight %
1-Butene, polymer with ethene	25087-34-7	98.0 - 100.0 %

Contains: Additives and stabilizers

SECTION 4. FIRST AID MEASURES**First aid procedures**

General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air.
Obtain medical attention.
Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)

In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer.
Do not attempt to peel polymer from skin as this will remove the skin.
Obtain immediate emergency medical attention if burn is deep or extensive.

In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.

In case of eye contact with molten polymer:
Continuously flush eye(s) with cool running water for at least 15 minutes.
Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).
Immediately seek medical attention.

If swallowed : Adverse health effects due to ingestion are not anticipated.

Notes to physician

Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.

Hazards : Dust contact with the eyes can lead to mechanical irritation.

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Molten polymer may cause thermal burns.

Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5. FIRE-FIGHTING MEASURES**Flammable properties**

Autoignition temperature : > 572 °F (300 °C)

Lower explosion limit : The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.

Upper explosion limit : Not applicable.

Fire fighting

Suitable extinguishing media : SMALL FIRE:
Use dry chemical, CO₂, or water spray.

LARGE FIRES:
Use water spray hose nozzles from a safe location.

Unsuitable extinguishing media : None known.

Further information : Combustible particulate solid, will decompose under fire conditions.
Calorific Value: 8000 - 11000 kcal/kg
Fight fire from safe distance with hose lines or monitor nozzles.
Heat from fire may melt, decompose polymer, and generate flammable vapors.
Move containers from fire area if it can be done without risk.
Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.
Always stay away from tanks engulfed in fire.
Do not attempt to get on top of storage containers involved in fire.
Cool storage containers with large volumes of water even after fire is out.

Protective equipment and precautions for firefighters

Specific hazards during fire fighting : Keep away from heat and sources of ignition.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Special protective equipment : Wear approved positive pressure self-contained breathing

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

for fire-fighters

apparatus and firefighter protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Equip responders with proper protection.
Creates dangerous slipping hazard on any hard smooth surface.
Equip emergency responders with proper personal protective equipment (PPE)
Avoid generating dust.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Potential combustible dust hazard.
Polymer particles create slipping hazard on hard smooth surfaces.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
- Methods for containment /
Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk.
On water, material is insoluble; collect and contain as any solid.
All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.

SECTION 7. HANDLING AND STORAGE**Handling**

- Advice on safe handling : Material is in a pellet form.
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air.
Avoid dust accumulation in enclosed space.
Use dust collection systems designed per NFPA 654 to avoid dust accumulation.
Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard.
Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion
Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.
Metal containers involved in the transfer of this material should be grounded and bonded.
All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts.
After handling, always wash hands thoroughly with soap and

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

water.

When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10.

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Storage

Requirements for storage areas and containers

: Store in a dry location.

Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation.

Store away from excessive heat and away from strong oxidizing agents.

Keep container closed to prevent contamination.

Take measures to prevent the build up of electrostatic charge.

8. Exposure controls/personal protection**Control parameters****Ingredients with workplace control parameters****Occupational Exposure Limits**

Ingredients	CAS-No.	Type	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	15 mg/m3 total dust	US (OSHA) 2005	

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust		TWA	5 mg/m3 respirable	US (OSHA) 2005	
---	--	-----	--------------------	----------------	--

Consult local authorities for acceptable exposure limits.

Exposure controls**Engineering measures**

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

- Respiratory protection : Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Use appropriate respiratory protection where atmosphere exceeds recommended limits.
Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
- Hand protection : Wear gloves that provide thermal protection where there is a potential for contact with heated material.
- Eye and face protection : Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
- Skin and body protection : Wear suitable protective clothing.
- Hygiene measures : Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.
Use good personal hygiene practices.
Wash hands before eating, drinking, smoking, or using toilet facilities.

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Take off contaminated clothing and wash before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Physical state	: Pellets.
Color	: dark blue
Odor	: Slight.

Safety data

Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 572 °F (300 °C)
Decomposition temperature	: not determined
pH	: Not applicable.
Melting point/range	: 122 - 338 °F (50 - 170 °C)
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm ³
Water solubility	: Insoluble.
Partition coefficient: n-octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Remarks - Other information : No additional information available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No known reactivity hazards.

Chemical stability : Stable under normal conditions.

Conditions to avoid : Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Materials to avoid : Material may be softened by some hydrocarbons.

Hazardous decomposition products : Not expected to decompose under normal conditions.

Thermal decomposition : Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.

Hazardous reactions : Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Acute oral toxicity** : Not classified**Acute inhalation toxicity** : Not classified**Acute dermal toxicity** : Not classified**Skin corrosion/irritation** : Not a skin irritant.**Serious eye damage/eye irritation** : Not an eye irritant.
Mechanical irritation is possible.**Respiratory or skin sensitization** : Not classified**Chronic toxicity**

Component Name	NTP	IARC	OSHA
Carbon Black		2B	Present

Carcinogenicity : Not classified

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Contains component(s) listed by IARC as possibly carcinogenic to humans.
This material is encapsulated in a thermoplastic resin with limited release under normal conditions of use, transportation, and storage.

Germ cell mutagenicity :
Not classified

Reproductive toxicity

Effects on fertility /
Effects on or via lactation :
Not classified

Effects on Development :
Not classified

**Target Organ Systemic
Toxicant - Single exposure** : The substance or mixture is not classified as specific target organ toxicant, single exposure.

**Target Organ Systemic
Toxicant - Repeated
exposure** : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard : Not applicable.

12. ECOLOGICAL INFORMATION**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

Persistence and degradability

Biodegradability : Not expected to be biodegradable.

Bioaccumulative potential

Bioaccumulation : This material is not expected to bioaccumulate.

Mobility in soil

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Additional advice : This material is not volatile and insoluble in water.
Environmental fate and pathways

Results of PBT and vPvB assessment

Not applicable.

Other adverse effects

Additional ecological information : Ecotoxicity is expected to be minimal based on the low water solubility of polymers.
No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.

SECTION 13. DISPOSAL CONSIDERATIONS

Further information : All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
Recycle if possible.

This material is classified as a Non-hazardous Material by RCRA.

SECTION 14. TRANSPORT INFORMATION

Not regulated for transport

SECTION 15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material is not known to contain a chemical substance known to the State of California to cause cancer, reproductive, or developmental toxicity under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1333-86-4 Carbon Black

Other international regulations**Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACH status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been pre-registered or, where required under REACH, registered, and that we have the intention to proceed with their registration in accordance with the deadlines set forth in REACH. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.**SECTION 16. OTHER INFORMATION****Further information****HMIS Classification**

: Health Hazard: 0
Flammability: 1
Physical hazards: 0



Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1


Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

NFPA Classification

: Health Hazard: 0
Fire Hazard: 1
Instability: 0

**Other Information**

HMIS rating scale (0 = minimal hazard; 4 = severe hazard)

NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

Material safety datasheet sections which have been updated:

Revised Section(s): 15 November 10 2015

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data.

Information is correct to the best of our knowledge at the date of the SDS publication.

It is not a specification sheet nor should any displayed data be construed as a specification.

Before using a product sold by a company of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally.

SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

Users should review the applicable Safety Data Sheet before handling the product.

This product(s) may not be used in the manufacture of any of the following, without prior written approval by Seller for each specific product and application:

- (i) U.S. FDA Class I or II Medical Devices; Health Canada Class I, II or III Medical Devices; European Union Class I or II Medical Devices;
- (ii) film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned medical devices;
- (iii) packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration;
- (iv) tobacco related products and applications, electronic cigarettes and similar devices.

The product(s) may not be used in:

- (i) U.S. FDA Class III Medical Devices; Health Canada Class IV Medical Devices; European Class III Medical Devices;
- (ii) applications involving permanent implantation into the body;
- (iii) life-sustaining medical applications.

All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

In addition to the above, LyondellBasell may further prohibit or restrict the use of its products in certain applications. For further information, please contact a LyondellBasell representative.

Adflex, Adstif, Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Aquathene, Avant, Catalloy, Clyrell,

Hostalen CRP 100 RESIST CR W BLUE

Gen. Variant: SDS_US_GHS

Version 1.1

Revision Date 12/14/2015

Print Date 04/12/2017

SDS No.: BE9835

Disclaimer

Dexflex, Flexathene, Hifax, Histif, Hostacom, Hostalen, Indure, Integrate, Koattro, Lucalen, Luflexen, Lupolen, Metocene, Microthene, Moplen, Nexprene, Petrothene, Plexar, Pristene, Pro-Fax, Purell, Sequel, Softell, Starflex, Ultrathene, and Valtec are trademarks owned or used by the LyondellBasell family of companies.

Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Avant, Dexflex, Flexathene, Hifax, Hostacom, Hostalen, Integrate, Koattro, Lucalen, Lupolen, Microthene, Moplen, Nexprene, Petrothene, Plexar, Pristene, Pro-Fax, Purell, Sequel, Softell, Starflex, and Ultrathene are registered in the U.S. Patent and Trademark Office.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.