

## Technical Data Sheet

### *Polyflam* HP0364V2CSLB15623ORE



Polypropylene, Homopolymer

#### Product Description

*Polyflam* HP0364V2CSLB15623ORE is a Polypropylene Homopolymer material. Features include: Good Thermal Stability, High Heat Resistance, and Homopolymer.

#### Regulatory Status

For regulatory compliance information, see HP0364V2CSLB15623ORE [Product Stewardship Bulletin \(PSB\)](#) and [Safety Data Sheet \(SDS\)](#).

|                     |                                                                            |
|---------------------|----------------------------------------------------------------------------|
| <b>Status</b>       | Limited Issue                                                              |
| <b>Availability</b> | North America                                                              |
| <b>Attribute</b>    | Good Thermal Stability; High Heat Resistance; Homopolymer                  |
| <b>Forms</b>        | Pellets                                                                    |
| <b>Additive</b>     | Flame Retardant                                                            |
| <b>Application</b>  | Appliances; Communication Applications; Electrical/Electronic Applications |

| Typical Properties             | Nominal Value | Units             | Test Method |
|--------------------------------|---------------|-------------------|-------------|
| <b>Physical</b>                |               |                   |             |
| Melt Flow Rate                 | 18            | g/10 min          | ASTM D1238  |
| Density - Specific Gravity     | 0.943         | g/cm <sup>3</sup> | ASTM D792   |
| <b>Mechanical</b>              |               |                   |             |
| Tensile Strength at Yield      | 33.1          | MPa               | ASTM D638   |
| Flexural Modulus               | 1520          | MPa               | ASTM D790   |
| <b>Impact</b>                  |               |                   |             |
| Notched Izod Impact, (3.18 mm) | 43            | J/m               | ASTM D256   |
| <b>Thermal</b>                 |               |                   |             |
| RTI Str, (1.6 mm)              | 100           | °C                | UL 746B     |
| <b>UL Information</b>          |               |                   |             |
| Flame Rating                   |               |                   |             |
| (1.6 mm)                       | V-2           |                   | UL 94       |
| (0.76 mm)                      | V-2           |                   | UL 94       |

## Notes

These are typical property values not to be construed as specification limits.

## Processing Techniques

Specific recommendations for resin type and processing conditions can only be made when the end use, required properties and fabrication equipment are known.

## Company Information

For further information regarding the LyondellBasell company, please visit <http://www.lyb.com/>.

© LyondellBasell Industries Holdings, B.V. 2018

## Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative.

## Trademarks

The Trademark referenced within the product name is owned or used by the LyondellBasell family of companies.